




DIN741




- **Materials** : Bridge : Casted
U-bolt : Mild steel
- **Standard** : DIN 741
- **Finish** : Electro-galvanized
- **Certification** : A works certificate can be supplied upon request

diameter wire rope	diameter bow	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
mm	a	b	c	d	e	f	g	kg
3	4	20	9	12	21	10	10	1.4
5	5	24	11	13	23	11	10	1.5
6	5	28	13	15	26	12	11	2.1
8	6	34	16	19	30	14	15	4.1
10	8	42	19	22	34	18	17	6.8
11	8	44	20	22	36	19	18	7.2
13	10	55	24	30	42	23	21	13
14	10	57	25	30	44	23	22	13.5
16	12	63	29	33	50	26	26	21
19	12	75	32	38	54	29	30	28
22	14	85	37	44	61	33	34	40
26	14	95	41	45	65	35	37	44
30	16	110	48	50	74	37	43	66
34	16	120	52	55	80	42	50	85
40	16	140	58	60	88	45	55	104



C-450D



- **Materials** : Drop forged high tensile steel
- **Standard** : Formerly U.S. Federal Specification FF-C-450D
- **Finish** : Hot dipped galvanized
- **Certification** : A works certificate can be supplied upon request.

diameter wire rope	diameter bow	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
inches	a	b	c	d	e	f	g	kg
1/8	5	24	12	11	24	21	10	2
3/16	6	31	15	13	29	24	13	4
1/4	8	34	19	13	37	30	18	8
5/16	10	45	22	19	43	33	19	14
3/8	11	49	26	19	49	42	25	19
7/16	12	60	30	25	58	46	26	31
1/2	13	61	30	25	58	48	31	34
9/16	14	72	33	32	63	52	31	36
5/8	14	74	33	32	64	54	36	45
3/4	16	86	38	37	72	57	38	68
7/8	19	98	45	41	80	62	40	108
1	19	108	48	46	88	67	47	113
1 1/8	19	117	51	51	91	73	48	140
1 1/4	22	130	59	54	105	79	56	207
1 3/8	22	140	60	59	108	79	58	234
1 1/2	22	147	66	60	112	85	64	266
1 5/8	25	161	70	67	121	92	67	329
1 3/4	29	174	78	70	134	97	76	441
2	32	195	86	78	150	113	85	603
2 1/4	32	213	98	81	162	116	100	707
2 1/2	32	227	105	87	168	119	113	806
2 3/4	32	243	112	91	174	127	124	1000
3	38	271	121	98	194	135	136	1440